

ALL STEEL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge to (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
RB15-712	matte	15	275	25	13	11	7.6	750	450	712	38x15.5R15
RB7501	pebble	16	300	25.0	14.0	10.0	8.0	650	370	528	7.50R16
RB7501L	matte	16	300	25.0	13.0	10.0	8.0	650	371	530	7.50R16
LL17	matte	16	300	28.4	12.7	12.0	9.0	590	414	513	LT235/85R16
LL16	matte	16	300	28.4	12.7	12.0	9.0	635	476	588	8.25R16
RB13001	matte	16	310	24.0	12.0	11.0	8.5	810	460	736	13.00R16
15AP474MAI	pebble	16	285	21.0	12.0	10.0	5.0	582	336	471	BS tire
B825-160A	matte	16	285	21.0	12.0	11.0	5.0	636	320	491	BS tire
B325x407x600	matte	17.5	325	24.0	14.0	12.0	7.0	600	407	505	
R175-529	pebble	17.5	295	23.0	14.0	10.0	8.0	570	425	529	265/55R17.5
R175-478A	matte	17.5	306	28.0	14.0	11.0	8.0	590	374	478	9.5R17.5
R195-499A	pebble	19.5	340	26.0	14.0	11.0	8.0	650	380	499	8R19.5
B825-181A	matte	20	356	28.0	15.0	15.5	5.0	730	362	537	BS tire
RB8251	pebble	20	374	25.0	13.0	11.0	7.5	740	376	540	
RB8251-2	matte	20	374	26.0	13.0	11.0	8.0	740	376	539.6	8.25R20
RB9001	matte	20	380	24.0	12.0	12.5	9.0	660	570	650	9.00R20
RB9002-1	pebble	20	380	24.0	13.0	12.0	9.5	710	540	650	9.00R20
RB9002-2	smooth	20	380	23.0	14.0	11.0	10.0	710	540	660	9.00R20
RB9003	matte	20	380	24.0	14.0	13.0		830	470	670	9.00R20
RB9004	smooth	20	374	21.0	12.5	12.0	11.0	730	440	594	9.00R20
RB10001	matte	20	380	24.0	14.0	13.0	8.0	830	470	670	10.00R20
RB10001-3	gravel	20	380	26.0	14.0	12.0	8.0	830	470	670	10.00R20
RB10002	matte	20	374	22.0	13.5	12.0		828	470	680	10.00R20
RB11001	matte	20	374	21.0	13.0	11.0	8.5	828	540	750	11.00R20
RB11002	matte	20	380	24.0	14.0	12.0		850	540	744	11.00R20
RB12002	matte	20	380	24.5	13.5	12.0		710	620	765	12.00R20
RB12003	matte	20	380	24.0	14.0	12.0	8.0	850	540	744	12.00R20

ALL STEEL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge to (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
RB12003-1	gravel	20	380	26.0	14.0	12.0	7.5	850	540	744	12.00R20
RB14002	matte	20	380	24.0	14.0	13.5	8.5	830	658	860	14.00R20
B10-237A	smooth	20	360	28.0	15.5	15.5	10.0	830	474	680	BS tire
B11-272A	smooth	20	360	28.0	15.5	15.5	10.0	830	544	750	BS tire
20D	matte	20	375	28.0	14.0	14.0	10.0	571	650	696	South tire
LL15	matte	20	384.2	28.4	12.7	12.7	8.0	762	556	686	
R225-630A	smooth	22.5	412	28.0	15.0	15.5	10.0	812	480	644	BS tire
RB225-611	smooth	22.5	412	28.0	15.0	15.0	8.0	750	480	611	275/70R22.5
RB225-694	smooth	22.5	412	28.0	15.0	15.0	8.0	845	506	694	12R22.5
RB315A	pebble	22.5	380	28.0	14.0	13.0	8.5	850	590	783	315/80R22.5
RB315B	smooth	22.5	380	24.0	14.0	12.0	8.5	850	571	790	
RB225-740	matte	22.5	432	26.0	14.0	11.0	8.0	760	580	740	455/40R22.5 445/50R22.5
22.5F	matte	22.5	431.8	28.6	14.3	12.7	9.0	790	600	754.3	385/65R22.5
22.5A	matte	22.5	430	28.0	14.0	14.0	9.0	631	564	600	South tire
22.5D	matte	22.5	430	28.0	13.0	12.0	8.0	790	510	678	South tire
NLL4	matte	22.5	384	28.4	12.0	12.7	9.0	712	456	576	255/70R22.5
B1-1	matte	20	384	28.4	12.7	12.7	7.5	765	486	634	
B21	matte	20	384.2	28.4	12.7	12.7	7.5	840	590	777	
B3	matte	22.5	384.2	28.4	12.7	12.7	8.5	800	550	709	295/75R22.5
B6	matte	22.5	384.2	28.4	12.7	12.7	7.5	850	590	779	315/80R22.5
LL18	matte	22.5	384.2	28.4	12.0	12.6	8.5	718	386	517	8R22.5
B19	matte	22.5	384.2	28.4	12.7	12.0	7.5	800	550	707	
RB4251	smooth	22.5	432	29.0	14.3	12.7	8.5	930	610	864	425/65R22.5
24.5A-1	smooth	24.5	483	28.6	12.7	12.7		646	525.9	561	South tire
B2-1	matte	24.5	435	29.4	12.7	12.7	8.0	800	539	665	
RB12004	matte	24	470	26.5	14.0	11.0	8.0	945	527	740	12.00R24
RB12005	matte	22.5	412	28.0	15.0	15.5	8.0	940	470	741	12R24.5

ALL STEEL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge to (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
RB2851	gravel	24.5	460	28.0	14.0	12.0	8.0	880	430	632	285/75R24.5
RB2852	matte	24.5	470	27.0	14.0	12.0	8.0	850	444	611	
17.5R25	smooth	25	500	36.0	16.0	16.0	12.0	1025	520	801.39	17.5R25
23.5R25	pebble	25	512	36.0	16.0	16.0	12.0	1140	760	1075	23.5R25
29.5R25	smooth	25	520	36.0	16.0	16.0	12.0	1220	900	1274	
18R33	smooth	33	660	36.0	16.0	16.0	12.0	1380	778	1150	
AB-0		20	406	20.3	22.35	12.7	9.5	800	400		8.25R20
AB-1		20	408.8	20.0	23.6	13.5	9.5	864	450		9.00R20
AB-2		20	412.8	20.0	23.6	13.5	9.5	865	506.5		11/12R20
A19x410x900	pebble	22.5	386	20.0	22.4	12.0		900	515	870.0	Pirelli tire
A19x315x840	pebble	22.5	386.3	20.0	22.4	12.0		840	443.1	782	Pirelli tire
A19x445x900	pebble		386	20.0	22.4	12.0		900	545	900	Pirelli tire
A19x365x840	pebble		386.3	20.0	22.4	12.0		840	365	832	Pirelli tire