

SEMI-STEEL (PCR) B TYPE RADIAL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
RB5008	matte	8	134	15	8	7	6.5	320	210	291	5.00R8
RB6009	matte	9	150	18	10	8	6	360	250	336	6.00R9
RB10-A	pebble	10	150	18	10	8	5	360	274	372	195/55R10C
RB10-B	pebble	10	150	18	10	8	5	385	212	340	145R10
RB13-1	smooth	13	232	22.0	13.5	10.0	6.0	412.6	211	281	
RB13-2	pebble	13	232	22.0	13.0	10.0	6.0	460	265.8	353	
RB14	pebble	13	225	19.0	12.5	7.0	4.9	460	310	405	
RB3082	pebble	13	225	24.0	13.0	9.0	4.7	381	292	336	
RB3332	pebble	13	225	24.0	12.5	8.5	4.7	385	285	330	
RB14-0	pebble	14	250	22.0	13.0	9.5	6.2	455	254	345	
RB14-1	pebble	14	250	22.0	13.0	9.5	6.0	470	267.5	370	185/70R14
RB14-2	pebble	14	250	22.0	13.0	9.5	5.3	520	282	418	195/70R14
RB14-3	pebble	14	250	22.0	13.0	9.5	5.8	545	322.5	467	215/70R15
RB14-4	pebble	14	250	24.0	12.9	7.0	4.5	490	280	378	185/70R14
RB14-5	leather	14	250	22.0	12.0	9.0	4.5	485	298	392	
RB164	pebble	14	251	24.0	13.0	9.0	4.7	356	327	361	
RB1953	pebble	14	250	24.5	13.0	9.0	4.7	400	384	412	
RB15-2	pebble	15	276	21.0	12.0	9.0	7.8	505	405	485	235/75R15
RB15-3	smooth	15	277	21.0	13.0	9.0	5/4.5	546	187	369	195/55R15
RB15-5	block	15	285	24.0	12.0	7.0	4.8	565	330	456	205/70R15
RB15-6	leather	15	276	24.0	14.0	7.0	4.5	450	250	320	
RB16-0	pebble	16	299	24.0	12.7	9.0	6.7	588	297.4	471.6	7.00R16
RB16-1	pebble	16	299	22.0	12.7	9.0	7.9	510	411	485	
RB16-2	smooth	16	299	22.0	12.7	9.0	7.5	570	466.4	561	265/75R16
12.5x385x562	block	16	290	22.0	12.0	8.0	4.5	570	385	489	Pirelli tire
12.5x445x562	block	16	290	22.0	12.0	8.0	4.5	570	445	549	Pirelli tire
RB16-3	matte	16	310	21.0	12.0	7.0	5.5	690	444	605	285/75R16
RB16-4	leather	16	301	24.0	12.5	7.0	4.8	585	380	489	
RB16-5	leather	16	302	23.0	12.7	7.0	5.0	620	376	600	
RB16-6	leather	16	310	22.0	12.0	8.0	5.5	610	400	516	

SEMI-STEEL (PCR) B TYPE RADIAL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
RB16-7	leather	16	310	22.0	12.0	8.0	5.5	660	450	584	
RB16-8	leather	16	310	22.0	12.0	8.0	5.0	500	340	396	
RB16-9	leather	16	310	22.0	12.0	8.0	5.0	535	370	440	
RB17-1	block	17	336	24.0	12.0	7.0	4.6	525	280	360.5	215/40R17
RB17-2	grid	17	336	24.0	12.0	8.0	4.9	490	306	352	205/40R17
RB17-3	pebble	17	336	24.0	12.0	7.0	5.0	510	344	394	245/45R17
RB17-4	leather	17	336	24.0	12.0	8.0	6.0	746	465	660	37x12.5R17
RB17-5	pebble	17	336	22.0	12.0	8.0	4.5	435	240	275	Fulun tire
RB17-6	leather	17	336	24.0	12.0	7.0	4.5	475	318	351	
RB18	gravel	18	353	24.0	12.9	8.0	4.9	520	358	410	255/35R18
B14x350x560	pebble	18	350	22.0	14.0	9.0	4.8	560	350	426	Pirelli tire
B15x370x620	pebble	19	375	22.0	14.0	9.0	4.2	620	370	488	Pirelli tire
RB20	block	20	396	24.0	12.5	8.0	5.0	570	350	404	245/35R20
RB20-1	grid	20	396	24.0	13.0	8.0	4.8	630	400	490	275/45R20
RB20-550	leather	20	396	24.0	12.0	7.0	5.0	670	438	550	LT305/55R20
RB20-532	leather	20	396	24.0	12.0	8.0	4.5	660	438	532	33x12.5R20
RB20-441	leather	20	396	24.0	12.0	7.0	4.5	605	378	441	245/50R20
ZP353	pebble	14	255	21.3	13.5	9.3	4.2	470	254	336	Goodyear tire
ZP357	pebble	15	281	20.1	12.5	11.4	4.5	510	268	368	Goodyear tire
ZP357-2	pebble	15	285	21.5	11.7	9.5	4.7	535	325	429	
ZP334	pebble	16	311.15	21.4	14.0	9.5	4.0	482.6	347.1	382.2	Goodyear tire
RB1451	pebble	13	224	22.0	13.0	7.3	4.5	460	235	335	165/70R13
RB1451-4	pebble	13	224	21.0	13.0	7.3	5.3	440	235	335	165/70R13
RB1452-3	pebble	13	234	23.0	13.0	7.5	5.5	440	248	320	
RB1452-5	smooth	13	234	23.0	13.0	7.5	4.5	440	248	320	
P13D	grid	13	228	22.0	12.7	6.0	4.7	422	276.2	345.6	
RB1651	pebble	14	248	21.0	12.5	7.0	5.4/4.5	490	275	370	175/65R14
RB1851	pebble	15	277	21.0	13.0	7.0	5.4/4.5	550	325	435	
RB1951	pebble	15	285	21.0	12.0	7.0	6.0	500	310	393	
RB1952	pebble	16	310	21.0	12.0	7.0	5.3	475	296	351	195/45R16

SEMI-STEEL (PCR) B TYPE RADIAL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
RB2051	smooth	15	267	21.0	13.5	7.0	5.7	550	324	440	
RB2052	pebble	16	310	24.0	12.0	7.0	5.2	535	334	410	215/60R16
RB2053	pebble	15	285	22.0	12.0	6.5	4.5	508	360	423	
RB2152	gravel	18	356	23.0	12.0	7.0	5.0	500	310	351	215/35R18
RB2251	pebble	18	356	23.0	12.0	7.0	5.0	535	328	386	225/50R18
RB2252	pebble	16	310	21.0	12.0	7.0	4.9	560	350	444	225/60R16
RB2351	pebble	15	285	21.0	12.0	7.0	5.8	635	374	526	32*11.5R15
RB2352	smooth	16	310	21.0	12.0	7.0	4.0	680	380	549	
P14B	grid	14	250.95	24.0	12.9	6.0	4.5	420	290	357	South tire
16A	matte	16	300	23.0	10.0	7.0	6.4	426	383	420	South tire
20A	matte	20	400	24.0	12.9	6.0	4.3	495	350	360	South tire
P20C	grid	20	403	24.0	12.7	6.0	4.8	560	368	430	
P20D	grid	20	403	24.0	12.9	6.0	4.8	540	370	410	
P18B	grid	18	352.43	24.0	12.9	6.0	4.8	480	332	374	South tire
14-T-378	matte	14	258	22.8	13.4	11.0	4.5	472	308	378	
					11.9						
RB2651	pebble	17	336	21.0	12.0	7.0	6.0	670	420	559	265/70R17
RB2751	pebble	18	356	24.0	12.0	7.0	5.3	660	430	548	275/65R18
RB7001	pebble	16	310	21.0	12.0	7.0	6.0	635	324	473	215/85R16
P24A	grid	24	505	24.0	14.7	6.5	5.2	620	397.5	425	South tire
P15D	grid	15	276.4	24.0	14.7	7.0	4.8	450	264.8	335	South tire
P17C	grid	17	326.7	24.0	15.0	6.0	5.1	610	336	465	South tire
P24B	grid	24	505	24.0	14.7	6.5	5.4	645	453.5	496.3	South tire
P16H	grid	16	302	24.0	13.0	6.0	5.5	580	426	555	South tire
RB22	grid	22	454	24.0	12.9	8.0	5.0	655	420	498	305/40R22
RB22-1	pebble	22	454	24.0	12.9	8.0	4.7	550	300	326	225/30R22
P22A	grid	22	454	24.0	12.7	6.0	5.0	600	430	480	South tire
P22E	grid	22	454	24.0	12.9	6.0	4.9	600	340	378	South tire
P26A	matte	26	555	24.0	14.7	7.0	4.7	700	410	452	South tire
P28A	matte	28	590	24.0	14.7	7.0	4.9	790	455	522	South tire

SEMI-STEEL (PCR) B TYPE RADIAL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
FL30	pebble	30	606	24.0	14.7	7.5	5.0	740	398	445	
RB12-307	leather	12	223	23.0	12.5	8.0	4.5	415	236	307	
RB12-318	leather	12	223	23.0	12.5	8.0	4.5	430	236	318	
RB13-392	leather	13	226	23.0	13.0	7.5	4.5	425	319	392	190/530R13
RB13-447	leather	13	226	23.0	13.0	7.5	4.5	440	365	447	240/550R13
RB13-305	pebble	13	226	22.0	14.0	9.0	6.0	425	246	326	Indonesia tire
RB13-345	pebble	13	226	22.0	14.0	9.0	6.0	460	270	366	Indonesia tire
RB13-370	pebble	13	226	22.0	14.0	9.0	6.0	460	295	392	Indonesia tire
RB14-370	pebble	14	250	22.0	14.0	9.0	6.0	480	300	391	Indonesia tire
RB14-415	pebble	14	250	22.0	14.0	9.0	6.0	520	330	437	Indonesia tire
RB14-412	leather	14	250	22.0	14.0	8.5	4.5	480	319	411	
RB14-450	leather	14	250	22.0	14.0	9.0	4.5	550	345	472	
RB15-415	leather	15	276	24.0	12.5	8.0	4.5	520	320	415	
RB15-430	leather	15	276	22.0	12.0	7.0	4.5	495	340	430	245/45R15
RB15-501	leather	15	276	24.0	12.5	8.0	4.5	560	400	501	
RB17-539	leather	17	336	24.0	12.0	8.0	5.5	630	445	539	
RB17-433	leather	17	336	24.0	12.0	7.0	4.3	565	344	433	225/60R17
RB18-467	leather	18	353	24.0	12.5	7.0	4.2	600	367	467	255/60R18
RB18-380	leather	18	356	24.0	12.0	7.0	4.2	540	310	380	
RB18-404	leather	18	356	24.0	12.0	7.0	5.0	585	300	404	
RB19-1	leather	19	380	24.0	14.0	8.0	4.5	520	310	356	
RB19-2	leather	19	380	24.0	14.0	8.0	4.5	520	340	382	
RB20-699	leather	20	396	24.0	12.0	8.0	5.5	755	572	699	38x15.5R20