

SEMI-STEEL AB TYPE RADIAL TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Foot LD	Foot height	Applied Tyres
RAB10x208x500	pebble		240	14.5	16	8.5	502	271	467	66	41	
RAB10x215x510	pebble	13	240	14.5	16.0	9.0	510	279	468	66	41	
RAB10x250x515	pebble	13	240	14.5	16.0	9.0	515	325	521	66	41	
RAB12x243x515	pebble	16	285	14.5	15.0	9.0	515	310	457	66	41	
RAB12x262x530	pebble	16	285	14.5	15.0	9.0	530	353	481	66	41	
RAB12x247x555	pebble	16	285	14.5	15.0	9.0	555	320	461	66	41	
RAB12x292x600	pebble	16	285	14.5	15.0	9.0	600	370	565	66	41	
RAB12x308x635	pebble	16	285	14.5	15.0	9.0	635	396	609	66	41	
RAB12x253x640	pebble	16	285	14.5	15.0	9.0	640	345	581	66	41	
RAB17x240x530	pebble		336	19.0	23.0	11.7	530	320	480	66	41	
RAB12x233x495	pebble		285	14.5	15.5	9.0	495	300	422	66	41	
RAB15x334x694	pebble	16	310.5	12.5	17.3	8.0	694	430	720	66	41	
RAB1451	pebble	12	262	12.5	13.5	7.0	450	240	350	98	32.5	
RAB1452	pebble	12	262	12.5	13.5	7.0	460	260	340	98	32.5	145R12
RAB1453	pebble	12	262	12.5	13.5	7.0	435	226	296	98	32.5	145R12
RAB1652	pebble	13	262	12.5	13.0	7.3	470	280	410	98	32.5	165R13
RAB1551	pebble	13-14	262	13.5	14.0	7.0	490	265	390	88	42	
RAB1651	pebble	14-15	262	13.5	14.0	7.0	520	305	455	88	42	
RAB1851	smooth	15-16	262	13.5	14.0	7.0	550	345	530	88	42	
RAB2451	smooth	16	262	13.5	14.5	7.5	590	385	580	88	42	
RAB7001	smooth	16	292	15.5	17.0	10.0	600	320	505	66	39.5	
RAB7501	pebble		285	14.5	15.0	8.0	670	347	604	66	41	7.50R16
RAB1852	pebble		240	14.5	16.0	9.0	510	330	438	66	41	185/65R14
RAB1951	pebble		240	14.5	16.0	9.0	540	353	485	66	41	195/65R15
RAB2151	pebble		240	14.5	16.0	9.0	577	343.5	520	66	41	215/75R14C