

## OTR / AGR TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
DK3330	pebble		384	29.0	13.0	14.0	630	897	950	20-20
DK3800	pebble		384	29.0	13.0	14.0	630	1067	1120	
B24A	pebble	24	500	28.0	13.0	13.0	600	492	515	9.5-24
B24B	pebble	24	500	28.0	13.0	13.0	620	550	580	11.2-24
B24C	pebble	24	500	28.0	13.0	13.0	650	595	628	12.4-24
B24D	pebble	24	495	28.0	13.0	13.0	590	406	428	8.3-24
B14.9-24	pebble	24	444.5	32.0	16.0	15.5	695	710	776	14.9-24
B12004(DK3737)	matte	24	470	28.0	12.0	12.5	662	616	680	12.00-24
B12005(DK3266)	pebble	24	470	28.0	13.0	13.0	714	706	780	12.00-24
B15001	gravel	24	460	28.5	14.0	15.5	770	872	996	15.00-24
B1751(DK1491)	gravel	25	470	28.0	12.5	13.0	714	850	910	17.5-25
B1752	pebble	25	470	36.0	15.5	18.0	714	802	880	17.5-25
B2051(DK1738)	gravel	25	470	38.0	15.5	23.0	830	990	1090	20.5-25
B2351(DK1758)	gravel	25	470	36.0	14.5	22.5	830	1100	1200	23.5-25
B2352	pebble	25	470	38.0	14.5	23.0	830	1100	1196	23.5-25
B2651(DK4462)	gravel	25	470	38.0	15.5	23.2	890	1350	1450	26.5-25
B301(DK26334)	gravel	25	470	38.0	15.0	23.5	890	1454	1550	29.5-25/29
B301-2	pebble	25	470	38.0	15.0	23.5	890	1694	1790	66x44.00-25
B11.2-28	pebble	28	530	30.0	14.0	13.0	680	580	620	11.2-28
B12.4-28	pebble	28	530	29.0	14.0	13.0	725	656	717	12.4-28
B14.9-28	pebble	28	530	29.0	14.0	13.0	725	760	821	14.9-28
B1691	matte	28	587	29.0	12.0	16.2	790	807	858	16.9-28
B1692	pebble	28	587	30.0	13.0	16.5	790	808	856	16.9-28
B18.4-28	pebble	28	587	32.0	14.0	15.0	860	902	963	18.4-28
B1841	gravel	30	600	28.5	14.0	16.0	930	900	1010	18.4-30
B1842	pebble	30	609	31.0	15.0	14.5	862	906	943	18.4-30
B23.1-30	pebble	30	600	32.0	15.0	14.0	860	1120	1174	23.1-30
B9.5-32	pebble	32	680	30.0	14.0	13.0	770	517	540	9.5-32
B11-32	pebble	32	630	30.0	15.0	14.0	845	660	714	11-32
DK5421	gravel	32	686	29.0	13.5	12.7	889	1230	1269	24.5-32
B30.5	gravel	32	686	29.0	13.5	12.7	1050	1300	1397	30.5-32
DK762	pebble	33	645	32.0	15.0	14.0	850	510	585	445/40D762
DK6571	gravel	33	648	39.0	15.5	23.0	959	1092	1163	18.00-33
B35/65-33	pebble	33	648	39.0	15.5	23.0	1085	1530	1648	35/65-33
B34-1	pebble	34	716	32.0	16.0	15.0	905	774	820	385/85R34
B1843	pebble	34	716	30.0	16.0	15.3	960	940	979	18.4-34
B1844	pebble	34	600	30.0	18.0	17.5	862	936	1004	18.4-34
B12.4-36	pebble	36	726	32.0	15.0	14.0	840	680	712	12.4-36
B21.00-35(DK10770)	pebble	35	647.5	39	16	23	1050	1330	1470	24.00-35
B11.2-38	pebble	38	827	26	13	13	940	560	596	11.2-38
B1241	matte	38	827	25.0	12.5	11.2	1020	634	693	12.4-38
B1502	pebble	38	827	25.0	12.0	13.5	1020	700	756	15.0-38
B38	pebble	38-42	838	29.0	13.0	14.0	1160	1130	1207	650/65R38
B1845	pebble	42	850	36.0	15.0	16.0	1120	880	918	18.4-42
B46-1	pebble	46	930	32.0	14.5	14.0	1170	910	965	
B46-2	pebble	46	930	32.0	14.5	14.0	1170	1050	1105	
B46-3	pebble	46	930	32.0	14.5	14.0	1100	670	708	230/95R48
B46-4	pebble	46	930	32.0	14.5	14.0	1100	770	808	270/95R48
B46-5	pebble	46	930	32.0	14.5	14.0	1100	820	858	12.4R46
B2301	pebble	48	914	31.0	15.0	14.0	1150	430	516	230/95-48
B14.9-48	pebble	48	1030	32.0	15.0	14.0	1170	780	820	14.9-48
DK4011	pebble	49	953	39.0	15.5	23.0	1372	1590	1680	27.00-49
DK19195	pebble	45	902	39.0	15.5	23.0	1371	1845	1960	45/65-45
DK10408	pebble	51	952.5	39	15.5	23	1385	1998	2083	36.00-51
12.4-54	pebble	54	1130	38.0	15.5	20.0	1300	695	733	12.4-54
B54-1	pebble	54	1100	32.0	15.0	14.5	1300	460	518	