

BIAS A TYPE TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
A4001	matte	12	262	12.5	15	7	334	262	325	4.00-12
A5001	matte	12	262	12	14	6.5	350	334	367	5.00-12
A5601	pebble	13	262	13.5	14	7.5	385	390	438	5.60-13
A6501	smooth	14	262	12.5	13	6.5	380	420	480	6.50-14
A6502	gravel	14	262	13.5	14	7	420	394	456	6.50-14
A6503	leather	16	262	12	15.5	8.5	403	473	525	6.50-16
A6504	matte	16	262	12.5	15	7	420	471	525	6.50-16
A6505	matte	16	262	12.5	15.5	8	400	476	534	6.50-16
A6506	block	16	262	12	14.5	7.5	440	472	545	6.50-16
A6508	pebble	16	310	12.5	17.5	8	440	455	512	6.50-16
A6509	smooth	16	310	12	17	9.5	440	450	512	6.50-16
A65010	matte	16	310	12.5	17.5	9.5	440	470	520	6.50-16
A65011	gravel	16	310	12.5	18	10	443	457	522	6.50-16
A65012	matte	16	310	12	17	9	440	483	547	6.50-16
A7501	matte	16	310	12.5	18	9.5	510	485	593	7.50-16
A7001	smooth	20	350	18	21	10	520	466	563	7.00-20
A7502	matte	20	350	18	21	9.5	540	475	570	7.50-20
A8251	matte	16	310	12.5	18.5	9.5	520	526	630	8.25-16
A9001	matte	20	395	18	21.5	11	590	567	660	9.00-20
A9002	smooth	20	425	17.5	24	12.5	635	540	678	9.00-20
A10001	smooth	20	429	20	22.5	12.5	638	649	764	10.00-20
A11001	smooth	20	429	20	22.5	12.5	638	649	764	11.00-20
A12001	smooth	20	429	20	22.5	12.5	638	675	814	12.00-20
A13061	smooth		270	14	15	8.5	550	600	707	Aircraft tire
A20051	matte		427	18	21	12	755	604	760	Aircraft tire
A3.00-10	matte	10	185	12.5	14.5	7	298	332	380	
TA20-1	smooth	20	425	20.3	22	12	580	590	814.5	9.00-20
										11.00-20
TA20-3	smooth	20	425	20.3	22	12	640	704	925.1	10.00-20