

BIAS B TYPE TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
B4001	gravel	4	42	16.0	6.5	6.5	108	240	252	4.00-4
B4002	gravel	4	42	19.5	6.0	9.0	116	276	294	4.00-4
B4003	pebble	4	42	16.0	7.0	6.5	113	186	212	4.00-4
B6x2	smooth	4	42	14.0	5.5	6.0	82	100	107	6x2
175x40	smooth	4	57	12.0	5.5	6.0	97	100	110	
B2.50-4	smooth	4	57	12.0	5.5	6.0	125	132	153	2.50/2.80-4
B200x50	smooth	4	57	12.0	5.5	6.0	100	113	124	200x50
B4007	pebble	4	56	16.0	7.0	6.5	115	195	209	3.50-4
B4004	pebble	5	67	16.0	6.0	6.0	140	191	213	4.00-5
B4501	pebble	5	67	16.0	6.0	6.0	145	260	280	4.50-5
B6.5-5	block	5	65	16.0	6.0	6.0	170	320	348	6.50-5
B5001	pebble	6	84	18.5	8.0	6.5	150	217	227	5.00-6
B5003	pebble	6	84	18.8	8.5	8.0	150	248	260	5.00-6
B6001	gravel	6	84	18.0	6.5	7.0	152	324	338	6.00-6
B6002	gravel	6	84	18.5	8.0	7.0	152	303	314	6.00-6
B6003	gravel	6	84	18.5	8.0	7.0	153	320	346	6.00-6
B6004	gravel	6	84	18.5	8.5	8.5	155	320	348	6.00-6
B6005	gravel	6	84	18.5	8.0	8.0	155	316	348	6.00-6
B6006	gravel	6	84	19.0	8.5	7.0	174	320	348	6.00-6
B81	pebble	7	96	16.0	8.0	8.0	190	320	348	8.00-7
B87	pebble	7	96	16.0	8.0	8.0	190	350	378	
B83	gravel	7	96	15.0	9.0	7.0	190	380	410	
B4005	gravel	8	116	23.0	11.5	6.5	205	262	288	4.00-8
B4006	matte	8	150	16.0	8.0	7.0	230	240	260	
B4801	matte	8	150	15.0	8.0	7.0	252	288	314	4.80-8
B6501	pebble	8	114	22.0	11.5	9.0	230	322	358	6.50-8
B8501	pebble	8	114	22.0	12.5	8.5	210	434	462	8.50-8
B8502	pebble	8	114	22.0	11.5	8.5	210	434	462	
B9501	pebble	8	118	23.5	10.5	10.0	252	408	468	9.50-8
B84	smooth	8	134	15.0	8.0	7.0	260	280	316	5.00-8
B85	smooth	8	134	15.0	8.0	7.0	245	311	340	18x7-8
B86	smooth	8	134	15.0	8.0	7.0	240	234	262	
9-400	pebble	8	138	22.0	11.0	10.0	275	340	366	
10-464	pebble	9	157	21.0	9.0	9.0	307	400	427	
B9"-1	pebble	9	165	17.0	9.7	9.0	305	450	486	
B9-2	matte	9	165	20.0	9.7	9.0	305	321	358	6.00-9
B10"-1	pebble	10	167	22.0	9.0	9.0	265	355	384	
B65010	pebble	10	165	22.0	11.0	9.0	345	354	400	6.50-10
B23910	pebble	10	165	22.0	11.0	9.0	345	390	435	
B11"-1	pebble	11	200	21.0	12.5	11.0	350	385	420	
B12"-1	pebble	12	220	21.0	12.5	11.0	370	450	481	8.25-12
B12-2	pebble	12	220	21.0	12.5	11.0	380	398	436	7.00-12
B12-3 (B12-2A)	pebble	12	220	21.0	12.5	11.0	360	520	550	
B12-4	pebble	12	220	22.0	12.0	9.0	320	290	316	4.50-12
B12-5	pebble	12	228	18.0	9.0	9.0	330	300	327	5.00-12
130/90-15	pebble	15	295	15.0	12.0	8.0	420	235	305	130/90-15
140/90-15	smooth	15	313	14.0	7.0	7.0	400	300	320	140/90-15
B5002	pebble	12	228	20.0	12.0	9.0	346	300	332	5.00-12
B6007	gravel	12	220	21.5	12.5	8.5	378	300	340	6.00-12

BIAS B TYPE TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
B6008	gravel	12	236	22.0	10.0	7.0	323	320	342	6.00-12
B6009	gravel	14	220	21.0	12.0	8.3	378	341	380	6.00-14
B6228	matte	13-15	218.4	20.8	12.7	9.7	386.1	346.5	410	
B6297	matte	14	247.7	20.8	12.7	9.7	405.9	464.3	496.8	
B6319	gravel	15	276.4	21.8	12.7	9.7	444.5	468.9	537.5	10-16.5
B6391	matte	15	276.4	21.8	12.7	9.7	409.2	463.6	499.4	
B16424	pebble	15	276	25.0	12.5	10.0	420	440	482	
B165A	pebble	15-16.5	276	24.0	15.0	10.0	440	530	570	12-16.5
B165B	pebble	16.5	276	24.0	15.0	10.0	440	464	515	
B400/60-15.5	smooth		276	24.0	12.0	10.0	500	640	700	400/60-15.5
B6502	gravel	14	260	24.0	13.0	10.5	405	400	442	6.50-14
B14-1	pebble	14	260	21.0	12.5	11.0	395	465	499	10.00-14
B14-2	pebble	14	260	20.0	8.0	8.0	350	280	304	20x6-14
B14-5	pebble	14	260	21.0	12.5	11.0	410	610	643	29x14-14
B6503	matte	16	310	25.0	12.5	10.0	437	380	408	6.50-16
B6504	pebble	16	310	25.0	13.5	10.0	437	380	408	6.50-16
B6505	smooth	16	310	25.0	13.0	8.0	456	380	410	6.50-16
B6506	pebble	16	310	24.0	12.0	9.0	435	400	420	6.50-16
B6507	leather	16	310	24.5	13.5	10.0	396	422	432	6.50-16
B6508	matte	16	310	22.0	11.5	10.0	480	400	450	6.50-16
B6509	pebble	16	310	23.0	13.0	10.0	430	346	384	6.50-16
B7001	pebble	14	280	23.0	11.5	9.5	430	412	450	7.00-14
B7002	matte	15	300	24.0	12.0	11.0	430	416	454	7.00-15
B7003	pebble	16	310	23.0	11.5	8.0	445	402	432	7.00-16
B7004	pebble	15	300	24.0	12.0	11.0	390	408	428	28x9-15
B161A	pebble	16.1	300	26.0	14.0	12.0	565	846	902	18.4-16.1
B161B	pebble	16.1	310	27.0	13.0	13.0	470	705	744	
B161C	pebble	16.1	310	26.0	12.5	12.0	510	820	867	
B7501	smooth	16	310	25.0	13.0	8.0	486	450	492	7.50-16
B7632	matte	13-15	218.4	20.8	12.7	9.7	386.1	407.9	473.5	
B82	smooth	14.5	267	22.0	13.5	8.0	431	400	434	8.00-14.5
B12-16.5	pebble	16.5	310	25.0	13.0	8.0	500	600	644	12-16.5
B90013	matte	16	300	24.0	12.0	11.0	520	520	576	9.00-16
B15-19.5	pebble	19.5	306	30.0	15.0	13.0	495	730	750	15-19.5
B8251	matte	20	360	27.5	14.5	13.0	480	520	556	8.25-20
B8252	matte	20	360	28.0	14.0	12.8	536	610	664	8.25-20
B8253	pebble	20	380	27.5	13.5	14.0	576	560	602	8.25-20
B9001	matte	20	360	27.0	13.5	13.0	620	554	638	9.00-20
B9002	matte	20	360	27.0	15.5	13.0	620	554	638	9.00-20
B9004	smooth	20	360	28.0	14.0	12.0	600	580	635	9.00-20
B9005	smooth	20	310	24.0	13.0	13.0	580	600	681	9.00-20
B9006	matte	20	360	27.0	14.0	12.5	580	590	670	9.00-20
B9009	smooth	20	380	28.0	14.0	12.0	600	580	636	9.00-20
B90010	matte	20	380	26.5	14.0	13.5	590	584	648	9.00-20
B90011	matte	20	380	27.0	14.0	12.5	590	584	650	9.00-20
B90012	gravel	20	380	26.5	14.5	13.5	590	584	650	9.00-20
B10001	matte	20	360	26.5	14.0	13.0	630	626	734	10.00-20
B10002	matte	20	380	26.5	13.0	12.5	630	626	712	10.00-20
B11002	pebble	20	360	27.5	13.5	14.0	620	624	728	11.00-20

BIAS B TYPE TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
B11003	smooth	20	360	27.0	13.0	14.6	588	700	770	11.00-20
B3851	pebble	22.5	360	28.0	14.0	12.0	560	740	793	385/65-22.5
B11004	pebble	20	380	27.0	14.0	13.0	620	624	708	11.00-20
B12001	pebble	18	340	27.0	13.5	13.0	623	650	764	12.00-18
B12002	gravel	20	380	26.5	13.5	12.7	660	690	792	12.00-20
B14001	matte	20	380	30.0	15.0	14.5	630	846	906	14.00-20
TB20-1	smooth	20	384	27.0	14.5	14.5	571	458.5	542	
TB20-3	smooth	20	384	27.0	14.5	14.5	650	548	630	
B1100-1	matte		275	22.0	10.0	8.5	430	645	687	
B850*250	matte		315	24.0	13.7		560	470	520	
B19011	smooth		360	27.5	14.0	13.5	594	630	686	Aircraft tire
B-LL1	matte	20	386	28.0	12.7	12.5	574	586	630	
B-LL2	matte	22.5	436	28.0	12.7	12.5	622	586	630	
B-LL3	matte	20	384	28.0	12.7	12.5	570	646	690	
B-LL4	pebble	20	384	28.0	12.7	12.5	570	461	512	
B-LL5	matte	22.5	384	28.4	12.7	12.7	572	525	576	
B-LL6	matte	22.5	384	28.4	12.7	12.7	588	647	697	
B-LL7	matte	19.5	340	28.4	12.0	12.0	490	442	476	
B-LL8	matte	17.5	310	28.4	12.0	12.0	460	426	460	
B-LL9	matte	22.5	384	28.4	12.7	12.7	588	719	770	
B-LL10	matte	19.5	340	28.4	12.0	12.0	498	472	508	
B-LL11	matte	17.5	310	28.4	12.0	12.0	460	470	504	
B-LL12	matte	22.5	384	28.4	12.7	12.7	675	746	825	
B-LL13	matte	19.5	340	28.4	12.0	12.0	510	494	538	
B-LL14	matte	24	435	28.4	12.7	12.7	720	700	771	
B950x300	matte		364	28.0	14.0	13.0	534	614	641	
1098#	matte		270	23.0	11.0	10.0	380	420	444	
1087#	matte		275	22.0	10.5	8.0	450	531	556	
B590x792	pebble		270	27.0	12.0	11.0	590	704	792	Aircraft tire
1115#	matte		360	24.0	12.0	11.0	480	380	417	
1118#	matte		220	22.0	10.0	10.0	330	395	422	
B1067	matte		260	24.0	13.0	10.0	440	510	545	
B1061	matte		296	28.0	14.0	13.0	514	580	619	
B1068	matte		248	24.0	12.0	9.0	372	352	370	
1131#	matte		270	24.0	10.0	10.0	520	740	814	