

BIAS C TYPE TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
C9001	smooth	20	140/380	28/26.5	14/13	12.5	590	592	778	9.00-20
C10001	matte	20	140/380	28/26.5	14/13	12.5	630	626	832	10.00-20
C12002	smooth	20	140/380	28/26.5	14/13.5	12.7	660	690	912	12.00-20
C12-16.5	pebble	16.5	140/310	28/25.0	14/13	8	500	600	644	12-16.5
RC31-1	smooth	15	170/225	21/21	12.0/12.0	8	560	524	656	
RC31-2	smooth	15	170/225	21.0/21.0	12.0/12.0	8	560	470	607	
TS-1	matte		170/225	24/24	12.0/12.0	7.6	470	248.4	379	
TS-2	pebble		170/225	24/24	12.0/12.0	7.6	490	279.4	418	
TS-3	pebble		170/225	24/24	12.0/12.0	7.6	500	302.4	444	
RM12-3	smooth		145/257	13.9/15.5	14.5/10	6.9	510	218.6	510	
RM12-4	smooth		145/257	13.9/15.5	14.5/10	7.5	545	229.4	545	
RM12-5	smooth		145/257	13.9/15.5	14.5/10	6.9	560	242.8	560	
RM12-9	smooth		145/257	13.9/15.5	14.5/10	6.9	495	235.4	540	
RM12-10	smooth		145/257	13.9/15.5	14.5/10	7	516	241.4	569.9	
RM12-11	smooth		145/257	13.9/15.5	14.5/10	6.9	537	252.4	593.3	
RM13-5	smooth		145/280	15.4/15.5	15.0/15.5	8.3	623	328.6	717.3	
HB3	smooth		170/225	23/23	11.0/11.0	7	450	350	441	Sourth Tire
RAB15	pebble	15	152/225	21.5/19.5	13.5/17.2	7.5	490	366	503	
B270-290x400x540	pebble		270/290	18.0/18.0	10.0/10.0	6	540	400	511	Pirelli tire
B270-290x295x475	pebble		270/290	18/18	10.0/10.0	6	475	295	375	Pirelli tire
B270-290x330x540	pebble		270/290	18/18	10.0/10.0	6	540	330	441	Pirelli tire
B270-290x300x540	pebble		270/290	18/18	10.0/10.0	6	540	300	411	Pirelli tire
B270-290x360x540	pebble		270/290	18/18	10.0/10.0	6	540	360	471	Pirelli tire
B270-290x296x515	pebble		270/290	18/18	10.0/10.0	6	515	296	396	Pirelli tire