

Bicycle/Motorcycle TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge to (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
B1101	block	10	183	13.0	8.0	6.0	6.5	248	300	326	110-10
B300-10	pebble	10	185	20.0	8.0	8.0	6.1	270	180	203	3.00-10
B3503	pebble	10	183	15.0	6.0	6.5	4.8	250	221	239	3.50-10
B60x230	matte		165	16.0	7.0	7.0	5.0	202	110	111	60x230
B1102	matte	16	335	12.5	9.0	6.0	6.2	405	264	284	110-16
B16x2.125	matte	12	235	16.0	7.0	6.5	6.3	285	139	152	16x2.125
B16x2.50	matte	12	235	16.0	7.0	7.0	6.3	285	159	172	16x2.50
B16x3.00	pebble	12	235	15.0	7.0	6.5	7.2	305	174	190	16x3.0
B9012	block	12	235	15.0	6.0	6.0	5.5	290	212	225	90/90-12
B4012	pebble	12	235	15.0	6.0	6.0	4.7	320	258	278	4.00-12
B1201	matte	12	235	15.0	8.0	7.0	5.8	298	240	258	120-12
B2251	matte	17	360	15.5	8.0	7.5	6.4	430	155	170	2.50-17
											2.25-17
B2007	pebble	17	360	16.0	8.0	7.0	5.8	430	102	118	2.00-17
B2252	pebble	17	367	20.0	7.0	7.0	4.8	430	134	145	2.25-17
B2751	matte	18	385	13.0	5.0	6.0	6.2	455	226	234	2.75-18
B2752	matte	14	284	15.5	8.0	7.5	6.4	355	178	193	2.75-14
B2753	pebble	18	392	20.0	7.0	7.0	5.0	448	168	178	80/100-18
B2754	pebble	18	390	15.0	7.0	6.0	4.8	430	186	192	2.75-18
B3001	matte	17	360	13.0	5.0	6.0	5.7	430	233	262	3.00-17
B3002	matte	18	385	14.0	5.0	6.0	6.1	455	226	234	3.00-18
B3003	matte	8	125	17.0	10.0	9.0	8.1	200	199	221	3.00-8
B9-3	pebble	9	165	20.0	9.0	8.0	5.8	230	195	208	120/50-9
B3004	pebble	18	392	20.0	7.0	7.0	5.0	448	197	206	3.00-18
B3251	matte	16	334	15.5	8.0	7.5	6.8	403	237	251	3.25-16
											110/90-16
B3501	matte	10	183	14.0	6.0	7.0	5.9	250	250	276	3.50-10
B3502	matte	17	360	13.0	5.0	6.0	5.5	430	233	262	3.50-17

Bicycle/Motorcycle TIRE CURING BLADDER

Bladder Code	Etch Type	Reference Bead Size (in)	Foot LD. dB (mm)	Foot height a (mm)	Foot width b (mm)	Foot gauge to' (mm)	Central gauge to (mm)	Outside Diameter DB (mm)	Over-all height HB (mm)	Effective periphery LB (mm)	Applied Tyres
ZX21	gravel	21	478	18	9	5		560	96	113	BC
ZC26	pebble	26	485	12	4	5		546	153	172	BC
40-559			490	14.5	9	5.5	4	558	74	93	
49-559			490	14.5	9	5.5	4	558	88	107	
54-559			490	14.5	9	5.5	4	558	98	117	
23-622			555	14.5	9	5.5	4	624	58	80	
37-622			555	14.5	9	5.5	4	624	76	98	
42-622			555	14.5	9	5.5	4	624	93	115	
B17-1	smooth	17	360	15	8	7	6.2	430	210	233	
80/90-17-1	pebble	17	360	14.5	7	6	6.6	428	187.5	204	
17/7.2i	smooth	17	367	20.0	7.0	7.5	5.4	430	174	185	
17/7.7i	smooth	17	367	20.0	7.0	7.5	5.2	430	184	195	
14/7.7i	matte	14	290	20	7	7.5	4.3	353	185	195	
70/90-14	matte	14	285	13.5	6.5	6.5	6	346	173	194	
80/90-14	matte	14	285	13.5	6.5	6.5	6	346	182	203	
90/90-14	pebble	14	285	14	6	6.5	5.8	346	215	235	
100/80-14	pebble	14	285	14	6	6.5	5.7	346	230	250	
60/80-17	matte	17	360	14	6.5	6.5	6.5	415	139	162	
70/90-17	matte	17	360	13.5	6.5	6.5	7.3	423	181	202	
80/90-17	matte	17	360	13.5	6.5	6.5	6.4	423	191	212	
90/80-17	pebble	17	360	14	6	6.5	6.6	423	181	198	
B19-1	matte	19	400	20	8	8	6.2	460	212	225	90/90-19
B37519	pebble	19	400	15	6	6	4.9	460	273	286	3.75-19
B13-1	pebble	13	260	16	7	7	6.2	315	220	232	130/60-13
B10x1.75	matte		94	15	7	7	6	143	118	132	10*1.75
B12x2.75	matte		145	15	7	7	6.2	195	176	189	12*2.75
B14x2.75	matte		195	15	7	7	6.4	245	176	189	14*2.75
B20x4.0	matte		310	20	12	9	7.8	380	224	241	20*4.0
B24x4.0			420	20	11	9	6.8	492	234	251	24x4.0